

am COLOUR GROUT

DESCRIPTION

am COLOUR GROUT is a cement-based tile grout and is suitable for interior and exterior application. It is used to fill joints between tiles or natural stones laid on walls or floors with its physical function of reducing stress within the whole wall or floor covering material. **am** COLOUR GROUT is integrally-coloured providing ease of installation and a durable grout for floor and wall tile application. It is formulated for residential, commercial or industrial applications and meets the requirements of BS EN 12808 specification.

ADVANTAGES

- Standard colours or custom matches upon request.
- Good adhesion to the edges of the tile and low-shrinkage.
- Good toughness, cohesion and low water absorption.
- Alkaline-resistant coloured and excellent workability.
- Does not deteriorate with ages.
- Available in sanded or non-sanded.

GROUT ADMIXTURE

am LATEX 330/302, multi-purpose acrylic polymer admixture improves the performance of **am** COLOUR GROUT. When mixed with grouts, **am** LATEX 330/302 increases flexural strength and tensile strengths, enhances colour (non-yellowing), virtually eliminates efflorescence, improves freeze/thaw resistance, acts as a waterproofing agent and helps the curing process.

APPLICATION

Grout should not be applied until 24 hours after tiling. Using a dense sponge or a rubber spreader, force the grout between the tiles, ensuring that all gaps are well filled. Using a clean sponge, wipe away excess grout and run a piece of dowelling along the grout lines to smooth and ensure a uniform thickness. When the grouts are dry, clean and polish the tiled area using a soft cloth.

HANDLING

am COLOUR GROUT is non-hazardous, but do wear protective clothing, and a filter mask to avoid inhaling dust. Remove splashes from skin with water. In case of eye contact, wash copiously with water. If irritation persists, seek immediate medical attention.

PACKING

am COLOUR GROUT is supplied in 5kg, 25kg

SHELF LIFE

If stored in a cool and dry place, the shelf life of **am** COLOUR GROUT is approximately 12 months in unopened bags.

TILE ADHESIVE AND STONE CARE

"A" Series Colour		"B" Series Colour		"C" Series Colour	
A1		B1		C1	
A2		B2		C2	
A3		B3		C3	
A4		B4		C4	
A5		B5		C5	
A6		B6		C6	
A7		B7		C7	
A8		B8		C8	
A9		B9		C9	
A10		B10		C10	
A11		B11		C11	
A12		B12		C12	

Tile Size (mm)	3mm Joint kg/m ²	6mm Joint kg/m ²	10mm Joint kg/m ²
025x025x06	2.8	N/A	N/A
050x025x06	1.8	N/A	N/A
050x050x06	1.2	N/A	N/A
075x075x06	2.3	3.7	5.6
100x100x06	1.7	2.5	3.6
100x100x10	1.9	3.0	4.8
100x100x13	2.5	3.8	5.6
100x200x10	1.4	1.9	2.6
100x200x13	2.0	2.8	3.8
150x150x10	1.3	1.8	2.5
150x150x13	1.6	2.2	3.0
150x150x19	2.0	2.8	3.8
200x200x06	0.8	1.1	1.5
200x200x10	0.9	1.4	2.0
200x200x13	1.7	2.2	2.9
250x250x10	0.4	0.6	0.9
300x300x06	0.6	0.7	0.9
300x300x10	0.7	0.9	1.2
300x300x13	0.9	1.1	1.6

The coverage for floor grout may be calculated by using the following formula :

Example:

Mosaics = 20mm x 20mm x 6mm, 3mm joint:
Coverage = 2.3kg/m²

Tiles = 150mm x 150mm x 9mm, 5mm joint:
Coverage = 1.0kg/m²

Natural Stone = 300mm x 300mm x 10mm, 3mm joint: Coverage = 0.3kg/m²



Asia Mortar Co., LTD (AM Co., LTD)

Tel: (84-028) 38 20 8686 Fax: (84-028) 38 20 8666

Email: amv@asiamortar.com.vn Website: www.asiamortar.com.vn

Revised 3-Aug' 2020



ISO 9001 : 2000 Cert.No. : 421453a

This information in this catalogue is provided to the best of our knowledge from results gathered both internal and external credited laboratories. However, we have no control over site applications, site conditions and workmanship of the applicator. We therefore will not accept any liability, either directly or indirectly arising from the misuse of these products or when the product is used not in accordance with any advice, specification, and recommendation of information given by us, The user is responsible for checking the suitability of these products for its intended use.

