

am GLASSFIBRE NETTING

DESCRIPTION

am Glassfibre Netting is designed to act as a strong reinforcement used in most waterproofing emulsion coating, joints on pre-fabricated panel wall, dry wall, plaster ceiling, and repair of cracks. Compared to the common chopstrains, **am** Glassfibre Netting reduces the constraint of working with loose and inconsistent distribution of strains. Hence, retaining the integrity of materials.

RECOMMENDED USES

- Used as reinforcement in waterproofing emulsion coating and crack repairs

ADVANTAGES

- High strength
- Will not trap air that cause blisters and bubbles
- Easy to handle
- Minimum wastage

TYPICAL PROPERTIES	
Odour and Appearance	Odourless cloth netting
Solubility	Non-soluble netting
Combustibility	Non-combustible
Density (counts per inch)	Warp: 10 x 2 Weft: 10
Gross Weight	Min. 50g per square meter
Minimum Tensile Strength	Warp: 400N per 50mm Weft: 420N per 50mm

PACKING

am Glassfibre Netting comes in 1m x 100m roll.



Asia Mortar Co., LTD (AM Co., LTD)

Tel: (84-028) 38 20 8686 Fax: (84-028) 38 20 8866

Email: amv@asiamortar.com.vn Website: www.asiamortar.com.vn

Revised 3-Aug' 2020



This information in this catalogue is provided to the best of our knowledge from results gathered both internal and external credited laboratories. However, we have no control over site applications, site conditions and workmanship of the applicator. We therefore will not accept any liability, either directly or indirectly arising from the misuse of these products or when the product is used not in accordance with any advice, specification, and recommendation of information given by us, The user is responsible for checking the suitability of these products for its intended use.

